

JERICHO

AIR POWERED HORN (INTEGRATED ELECTROVALVE)



REF. 928060

Main Specifications and performances

NOMINAL VOLTAGE	24 Vdc
VOLTAGE RANGE	16 - 32 Vdc
CURRENT CONSUMPTION	0,8 A
SOUND PRESSURE LEVEL	118 (2m) dB(A)
FREQUENCY	380 Hz
OPERATING TEMPERATURE	-30° to +85° °C
STORAGE TEMPERATURE	-30° to +85° °C
CORROSION RESISTANCE	>720 (salt spray test) Hours
OPERATING RELATIVE HUMIDITY	30 to 80 %
DURABILITY (1 sec ON, 4 sec OFF)	>500 000 Cycles
CONTINUOUS BLOWING	>30 min
ELECTRICAL INSULATION	500 Vdc
VIBRATION (30 min, 3 axis)	5 g
WEIGHT (each)	390 gr
MAIN MATERIALS	Steel, PA66
MAIN APPLICATIONS	Trucks, Bus, Trains

Conformity to Standards of

PRODUCT	REG. 28 ECE REG. 10 ECE
MANUFACTURING	IATF ISO 9001 ISO 14001

Other Specifications


MECHANICAL CONNECTION: flat and rigid surface facing the fixing point surface;

HORN'S PROTECTION: installation area protected from mud splash;

MASTER CARTON: 15 pieces;

Available Connections

ELECTRICAL CONNECTION:
Cable connection 2 blades



AIR CONNECTION:
Legris 6 mm

Dimensions (mm)

